



TELMA

TELMA RETARDER, INC.
3488 Diablo Avenue, Hayward, CA 94545
Tel: (510) 784-1048 • Fax: (510) 784-1288

TIL05044

Date: November 16, 1992

TECHNICAL INFORMATION

Subject: Minimum driveline lengths required for installation of chassis mounted retarders.

Model: CE and CC Series Retarders

Effective Date: December 16, 1992

Dana Driveline Series	Very Minimum Length <i>(Does not guarantee that the installation is possible)</i>	Desirable Length <i>(Drastically improves chances of installation)</i>	Most Desirable Length <i>(Almost always guarantee that installation is possible)</i>
1280/1310	28.25"	34.00"	34.00"
1350	28.625"	35.50"	35.50"
1410	27.08"	35.40"	42.70"
1480	25.50"	37.38"	37.88"
1550	27.00"	40.38"	40.38"
1610	28.25"	43.00"	45.69"
1710	31.00"	43.50"	46.00"
1810	35.75"	46.43"	50.00"
1880	36.25"	44.75"	51.00"

This document is the exclusive property of TELMA RETARDER INC. It cannot be copied, modified, forwarded, or given to any third party without prior agreement from TELMA RETARDER INC. Any infringement will immediately involve legal action.